

## SAFETY DATA SHEET

### PTFE- LUBRICANT POWDERS

Updating: 25/05/2005

#### COMPANY IDENTIFICATION

- Company name : **POLIS<sub>SRL</sub>**
- Address : Via Artigianale,19  
25020 – Cignano di Offlaga (BS) I
- Telephone and Fax nr : 030 – 979304 – 979989

#### **Emergency Calls**

- Telephone nr. : 030- 979304 – 979989

#### 1) COMPOUND IDENTIFICATION

- Trade Name : LUBRICANT POWDER ( **LUBEFLON<sup>®</sup>** )
- Grades : All Types
- Compound description : Polytetrafluoroethylene
- Structural formula :  
(of the polymer)  $-(CF_2-CF_2)_n-$
- CAS Name: Polytetrafluoroethylene
- CAS Number : 9002-84-0
- EINECS Number : not assigned
- ELINCS Number : not assigned
- INDEX Number : not assigned

#### 2) COMPOSITION / INFORMATION ON INGREDIENTS

Substances with established exposure limits or classifiable as dangerous according to EC Directive 67/548 and following amendments, in concentration equal or higher that that reported in EC Directive 88/379 (item.3, sect..6) :

<u>Name</u>	<u>Conc.</u>	<u>N° CAS.</u>	<u>Symbol</u>	<u>Risk phrases</u>
Polytetrafluoroethylene	100%	9002-84-0	-(CF <sub>2</sub> -CF <sub>2</sub> ) n-	-----

#### 3) HAZARD IDENTIFICATIONS

##### **3.1 Adverse human health effects**

- The product is an inert polymer, which is not dangerous for the human health

##### **3.2 Main symptoms**

- See section 4

##### **3.3 Environmental effects**

- Environmental pollution only in case of emission of toxic and corrosive gases following thermal decomposition.

##### **3.4 Physical and chemical hazards**

- Toxic and corrosive gases are released in thermal decomposition.

## SAFETY DATA SHEET

### ***PTFE- LUBRICANT POWDERS***

Updating: 25/05/2005

---

#### **4) FIRST-AID MEASURES**

##### **4.1 Symptomatology following exposure to products of thermal decomposition**

- Inhalation                      Headache, short breathing, cough, chills and fever , tachycardia.
- Eye contact                      Redness, irritation, burns
- Skin contact                      Redness, irritation, burns

##### **4.2 First Aid Measures in case of exposure to gases from thermal decomposition**

- Inhalation                      Move immediately affected person to fresh air.  
Seek medical attention immediately.  
If not breathing, supply artificial respiration, preferably mouth to mouth.  
In case of difficult breathing, give oxygen.  
The symptoms by inhalation of thermal decomposition products do not occur until several hours after exposure.  
Keep the affected person under medical observation for at least 48 hours.  
A timely medical attention is absolutely required.
  
- Eye contact                      Flush immediately and copiously with water for at least 15 minutes, retracting eyelids often.  
Seek medical attention in case burns continues.
  
- Skin contact                      Wash immediately with water and soap (pay particular attention to flushing skin under nails).  
Seek medical attention in case burns continues.

#### **5) FIRE FIGHTING MEASURES**

##### **5.1 Specific hazards**

- The product is neither flammable nor explosive.
- In the event of fire, corrosive and toxic gases from thermal decomposition may be formed.

##### **5.2 Specific methods**

- In case of surrounding fire, if possible, remove the containers in a safety place.  
To do only if in safe conditions (safety distance from the flames and staying upwind)
- In case of impending fire, keep containers cool by spraying with water.

##### **5.3 Extinguishing media**

- Water (spray, fog, stream), CO<sub>2</sub>, chemicals in powder or foam.

##### **5.4 Protection of fire-fighters**

- Self contained breathing apparatus.
- Full anti-acid clothing

## SAFETY DATA SHEET

### ***PTFE- LUBRICANT POWDERS***

Updating: 25/05/2005

---

#### **6) ACCIDENTAL RELEASE MEASURES**

##### **6.1 Personal precautions**

- Keep away from hot surfaces and flames.
- Stop the release as soon as possible, in safe conditions.

##### **6.2 Environmental precautions**

- Avoid uncontrolled discharge of the product in the soil and underground waters.

##### **6.3 Methods for cleaning up**

- Sweep and scoop out the released material, collecting it in suitable container for re-use or disposal according to applicable regulations.

#### **7) HANDLING AND STORAGE**

##### **7.1 HANDLING**

###### **7.1.1 Precautions**

- Wear suitable protective clothing (see par. 8)
- Avoid processing above decomposition temperature without adequate ventilation.
- Keep attention that particles of products coming from hands or from garments will not become in contact with materials or substances that could be burnt. (ex. cigarettes, tobacco)
- Clean facilities (pipe, vessels) before any discontinuous operations.

###### **7.1.2 Security measures**

- In working areas where the materials are handled at temperatures higher than 350°C appropriate exhaust ventilation and smoke down bringing are required .

##### **7.2 STORAGE**

###### **7.2.1 Storage conditions**

- Keep away from sparks and flames , hot surfaces and inflammable materials .
- Do not store near incompatible materials. (see par. 10).

###### **7.2.2 Packing**

- Polythene bags placed in cardboard boxes or plastic drums .

#### **8) EXPOSURE CONTROLS / PERSONAL PROTECTION**

##### **8.1 Exposure limits**

###### **ACGIH 2003**

- |                    |             |            |       |
|--------------------|-------------|------------|-------|
| • Total dust       | TLV/TWA     | 10 mg/mc   |       |
| • HF               | TLV/CEILING | 2,6 mg/mc  | 3 ppm |
| • COF <sub>2</sub> | TLV/STEL    | 13,5 mg/mc | 5 ppm |

##### **8.2 Technical measures**

- Adequate local exhaust ventilation is required in case of high temperature processing

##### **8.3 PERSONAL PROTECTIVE EQUIPMENT**

###### **8.3.1 Respiratory protection**

- Dust safety masks, self-contained breathing apparatus in case of fire

###### **8.3.2 Hand protection**

- Latex gloves or similars

###### **8.3.3 Eye and body Protection**

- In case of high dust concentration wear safety goggles and appropriate worksuits/overalls.

###### **8.3.4 Measures**

- Do not eat, drink or smoke while handling the product.

## SAFETY DATA SHEET

### ***PTFE- LUBRICANT POWDERS***

Updating: 25/05/2005

---

#### **9) PHYSICAL AND CHEMICAL PROPERTIES**

• Physical state	powder
• Odour	odourless
• Colour	white
• Bulk Density	250÷550 g/l
• Melting point	327 ÷ 335 °C
• Decomposition temperature	> 350 ° C
• Autoignition temperature	575 ° C
• Ph	not applicable
• Boiling point	not applicable
• Flash point	not flammable
• Explosion properties	not explosive
• Oxidising properties	not oxidiser
• Vapour pressure	not applicable
• Vapour density	not applicable
• Solubility in water	not soluble
• Solubility in organic solvents	not soluble

#### **10) STABILITY AND REACTIVITY**

##### **10.1 Stability**

- The product is stable in normal condition of use and storage.

##### **10.2 Conditions to avoid**

- Avoid heating the product above a temperature of 350 °C in absence of adequate protective measures
- Avoid contact with sparks and flames , hot surfaces and inflammable materials

##### **10.3 Materials to avoid**

- Avoid contact with alkaline metals and Fluorine under pressure.

##### **10.4 Hazardous decomposition products:**

- Toxic and corrosive vapour-steam(hydrogen fluoride, carbonyl fluoride, tetrafluoroethylene, hexafluoropropane and perfluoroisobutane).
- The temperature level influences directly the thermal combustion products

## SAFETY DATA SHEET

### PTFE- LUBRICANT POWDERS

Updating: 25/05/2005

#### **11) TOXICOLOGICAL INFORMATION**

##### **11.1 Penetration routes**

- Inhalation of toxic vapours or dust ingestion

##### **11.2 Adverse effects for the Human Health**

- Delayed and/or immediate effects after short and/or prolonged exposure: Health injuries are not known or expected under normal use.
- Acute toxicity: The thermal decomposition vapours of fluorinated polymers may cause Polymer fume fever with influenza-like symptoms (headache, tremors, sweating, high temperature), especially when smoking contaminated tobacco; danger of serious damage to health by prolonged exposure.
- Chronic toxicity: No data available in normal industrial documentation
- Local effects: May cause irritation to the eyes or skin due to mechanical effects  
Decomposition products may cause severe burns on skin, eyes and mucousae.
- Sensitisation: No data available
- Carcinogenicity: IARC Evaluation : Group 3 (the agent is not classifiable as to its carcinogenicity to humans)
- Mutagenicity and Reproduction toxicity: The product is not listed as potential mutagenic agent by National and International Agencies or Competent Authorities.

##### **11.3 Experimental toxicological data (on animals)**

- LC<sub>50</sub> – inhalation 3500 mg/m<sup>3</sup> (30 min.) Species : rat  
(referred to pyrolysis products of PTFE at 625 °C)
- LC<sub>50</sub> – inhalation 2700 mg/m<sup>3</sup> (5 min.) Species : rat  
(referred to pyrolysis products of PTFE at 800 °C)

#### **12) ECOLOGICAL INFORMATION**

##### **12.1 Environmental effects**

- Mobility and bioaccumulation: no data available
- Persistence: no data available
- Degradability: no data available
- Ecotoxicity: no data available

##### **12.2 Evaluation**

- Avoid polluting the environment

## SAFETY DATA SHEET

### PTFE- LUBRICANT POWDERS

Updating: 25/05/2005

#### **13) DISPOSAL CONSIDERATIONS**

##### **13.1 Waste treatment**

- The product that can not be recycled must be disposed in authorised landfill or destroyed in a high-temperature incinerator designed to burn halogen materials.

##### **13.2 Packaging treatment**

- Dispose of in authorised landfills according to local laws and regulations.

#### **14) TRANSPORT INFORMATION**

##### **14.1 Specific hazards**

- The product is not classified as dangerous in transportation

##### **14.2 Packaging information**

- Product usually shipped in plastic (PE) bags within plastic canisters.

##### **14.3 International transport classification**

- Packaging group: not assigned
- U.N. Number not assigned

#### **15) REGULATORY INFORMATION**

##### **15.1 EC Regulations**

- Directive 67/548 and following amendments

##### **15.2 Classification**

- Hazard class: none
- Classification type not required

##### **15.3 Labelling**

- Trade name LUBRICANT POWDER (LUBEFLON®)
- Types All Types
- Risk phrases ( R ) none
- Safety phrases ( S ) none
- Hazard Symbol none

#### **16) OTHER INFORMATION**

- Data Bases : IUCLID(1996) OHMTADS (2003) IRIS (2003) RTECS (2003) HSDB (2003)
- Safety data sheet according to Directive 2001/58/CE

*The information given in this safety data sheet is based on the present available knowledge.*

*Their aim is to describe the security appearance related to our products and not really to grant their properties.*

*The Company is not responsible for damages to persons or things caused by a misuse of the information indicated in this document .*